

# SHARP

**XG-F315X**  
True XGA Data Projector



**With DLP® Performance and New BrilliantColor™ Technology, Sharp's New Projectors Produce Incredible Reproduction of Vivid Colours and Fine Colour Nuances**

- 3 000 ANSI lumens
- BrilliantColor™ Technology
- Long-Life High-Performance DLP® Picture
- 2000:1 High-Contrast, High-Quality Image
- 3x Speed Colour Wheel
- IP Conversion from TrueVision™ Image Processing
- Low Fan Noise
- Double Sealed Mechanism
- Multiple Input Terminals
- HDTV/DTV and DVD Compatible
- Image Shift Function Images projected in 16 x 9 format can be vertically shifted for better viewing in limited spaces.
- Auto Keystone Correction
- Presentation Support: Freeze, AV Mute
- Theft Deterrent Function "System Lock"
- Key Lock Function
- Warranty 3 years



3000 ANSI lumens



# XG-F315X

Specifications		
Model		XG-F315X
Display devices		0.55" DLP® chip x 1
Resolution		XGA (1 024 x 768 )
Brightness		3 000 ANSI lumens
Contrast ratio		2 000:1
Lens	F number	F 2.4 - 2.6
	Zoom	Manual, x 1.15 (f = 18.7 - 21.5 mm)
	Focus	Manual
Input signals	DTV	1080P / 1080i / 720P / 576P / 576i / 540P / 480P / 480iNTSC 3.58 / NTSC 4.43 / PAL / PAL-M / PAL-N / PAL-60 / SECAM
	Computer RGB * Compression	UXGA* / SXGA+* / SXGA* / WXGA* / XGA / SVGA / VGA Mac 21"* / 19" / 16" / 13"
Input terminals	DVI-I (Compatible with HDCP)	x 1
	Computer / Component (mini D-sub 15 pin)	x 1
	S-Video (mini DIN 4 pin)	x 1
	Video (RCA)	x 1
	Audio (ø 3.5 mm stereo mini jack)	x 1
	Audio (RCA)	x 1 (L/R)
Output terminals	Computer / Component (mini D-sub 15 pin)	x 1
	Audio (ø 3.5 mm stereo mini jack)	x 1 (variable audio output)
Control and communication terminals	USB (Type B)	x 1
	RS-232C (mini DIN 9 pin)	x 1
Horizontal frequency		15 - 110 kHz
Vertical frequency		45 - 85 Hz
Speakers		2 W (mono)
Fan noise		35 dB (Bright), 30 dB (Eco + Quiet)
Projection lamp		275 W
Lamp life		3 000 hours (Eco + Quiet)
On-screen display languages		English, German, Spanish, Dutch, French, Italian, Swedish, Portuguese, simplified Chinese, Korean, Japanese, Russian, Arabic, Polish, Turkish
Rated voltage		AC 100-240 V
Rated frequency		50/60 Hz
Input current		3.7 A
Power consumption (standby)		363 W (10.5 W) with AC 100 V, 349 W (11.0 W) with AC 240 V
Operation temperature		41° F to 95° F (+5° C to +35° C)
Dimensions (main body only) W x H x D		12 13/32" x 4 19/64" x 11 1/32" (315 x 109 x 280 mm)
Weight (approx.)		9.1 lbs. (4.1 kg)
Supplied accessories		Remote control, two R-6 batteries, power cord (6' (1.8 m)), RGB cable (10' (3.0 m)), lens cap, DIN-D-sub RS-232C adaptor (5 57/64" (15 cm)), storage case, operation manual, CD-ROM

Design and specifications are current as of September 2007, but are subject to change without notice.

\* Compression response compatible

- DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments.
- All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers. Sharp makes no warranties or representations of any kind with respect to these products.
- The lamp life may vary depending on the usage condition.

Sharp Electronics (Nordic) AB

Box 14098 • 167 14 Bromma

Tel 08-634 36 00 • Fax 08-634 36 10

[www.sharp.se](http://www.sharp.se)

# SHARP