

Data's	
	ASV AGLR
Resolution in dots	1,920 x 1,080
Display colors	16.77 Million (8bit)
Brightness	450cd/m <sup>2</sup>
Displaying Mode	Normal Black
Response time in ms	6
Panel Size in mm	1152 x 648
Aspect ratio	2000:01:00
Viewing angle ( H / V )	176 / 176

Terminals	
Input	DVI-D(24pin) < DVI1.0> (HDCP Support ); RGB (mini D-Sub 15pin ); RGB (BNC x5)*; Component(Y, Pb/Cb, Pr/Cr :BNC)*; Composite (BNC) -NTSC/PAL/SECAM
Output	RS-232C Line in ( RCA x2) for AV; Line in 2 (3.5mm mini stereo jack) for PC

Output Terminals	
Input	DVI-D (24pin ) w/ HDCP
Output	RS-232C

Audio Data's	
Speaker	Line out (RCA x2)
Power out	7W 7W [6 Ohm]

Color Systems	
Color system	NTSC(3.58)/NTSC(4.43)/PAL/PAL60/SECAM

Compatible signal timing(PC)	
Compatible signal timing(PC)	Analog (Hsync 31.0 to 81.1 kHz, Vsync 56 to 76.2 kHz ); Digital (Hsync 31.0 to 80.0 kHz, Vsync 60 to 75 kHz )

Functions	
OSD controls	OSD; Remote control×1, IR Type; RS-232C
Display & play	VESA DDC2B
Control	Auto/ Manual
Image Adjusting	Digital scaling(VGA/SVGA/XGA/SXGA to Full HD)
OSD scale-down adjusting	•
OSD Equal Adjusting	Clock, Phase, Image Positioning, Black level, Contrast Ratio, Brightness, Color Temperature, Color Mode, Volume, Audio menu ( Treble, bass, balance), Remote control×1
OSD Languages	7 Languages (JPN, ENG, GER, FRA, ITA, ESP, RUS)
OSD Adjusting	•
Power-off timer	Yes by Scheduling Function
OSD Adjusting function	•
OSD Adjusting lock	•
OSD Multi-screen capability(Expansion)	Max 5 x 5
OSD Power-on delay	•
OSD Trace function	•
OSD Image adjustment	•
OSD Image reversing	Yes ( Up, down , left, right, all four directions)
OSD Image management	T.B.D
OSD Image control and display	VESA DPMS, DVI DMPM
OSD Image monitoring	Yes by RS-232C
OSD Multi-chain connection	Yes by DVI (Mirror/ Enlargement) up to 5 displays
OSD Label front bezel	•
OSD Portrait Orientation	•
OSD Power switch	•

Accessories	
Mounting method	VESA holes (M6 x 6, 200 mm pitch) (P)
Accessories	Power cable, Remote control, Utility disk(CD-ROM), Vertical logo, Temporary stand, Cable clamp, Power cord clamp, Operation manual, Blank sticker, 2 "AA" size batteries
Material	Front: Resin / Back : Aluminum; (Front bezel replacable)
Dimensions (W x D x H) with bezel in mm	1,572 x 126 x 923
Dimensions (W x D x H) without bezel in mm	1,255 x 132 x 743
Weight	65
Power consumption	550/2
Operating temperature	0 to 40
Operating Humidity	20% to 80% (No-condensing)
Input voltage	100V-240V
Model Code	4,97402E+12