

Data's	
Resolution	ASV AGLR
Resolution in dots	1,920 x 1,080
Display colors	16.77 Million (8bit)
Brightness	450 cd/m ²
Displaying Mode	Normal Black
Response time in ms	6
Panel Size in mm	1152 x 648
Aspect ratio	1800:01:00
Viewing angle (H / V)	176 / 176

Terminals	
Input	DVI-D(24pin) < DVI1.0> (HDCP Support); RGB (mini D-Sub 15pin); RGB (BNC x5)*; Component(Y, Pb/Cb, Pr/Cr :BNC)*; Composite (BNC) -NTSC/PAL/SECAM RS-232C
Output	Line in (RCA x2) for AV; Line in 2 (φ3.5mm mini stereo jack) for PC

Output Terminals	
Output	DVI-D (24pin) w/ HDCP RS-232C

Output Data's	
Line out	Line out (RCA x2)
Power out	7W 7W [60hm]

Systems	
Color system	NTSC(3.58)/NTSC(4.43)/PAL/PAL60/SECAM

Compatible signal timing(PC)	
Compatible signal timing(PC)	Analog (Hsync 31.0 to 81.1 kHz, Vsync 56 to 76.2 kHz); Digital (Hsync 31.0 to 80.0 kHz, Vsync 60 to 75 kHz)

Functions	
OSD controls	OSD; Remote control×1, IR Type; RS-232C
Display & play	VESA DDC2B
Control	Auto/ Manual
Image Adjusting	Digital scaling(VGA/SVGA/XGA/SXGA to Full HD)
Scale-down adjusting	•
Image Adjusting	Clock, Phase, Image Positioning, Black level, Contrast Ratio, Brightness, Color Temperature, Color Mode, Volume, Audio menu (Treble, bass, balance), Remote control×1
Languages	7 Languages (JPN, ENG, GER, FRA, ITA, ESP, RUS)
Image Adjusting	•
Power-off timer	Yes by Scheduling Function
Power saving function	•
Keypad lock	•
Multi-screen capability (Expansion)	Max 5 x 5
Power-on delay	•
Power save function	•
Image adjustment	•
Image reversing	Yes (Up, down , left, right, all four directions)
OSD management	T.B.D
OSD control and display	VESA DPMS, DVI DMPM Yes by RS-232C
OSD monitoring	Yes by DVI (Mirror/ Enlargement) up to 5 displays
OSD chain connection	•
OSD label front bezel	•
OSD tilt Orientation	•
OSD power switch	•

Specifications	
Mounting method	VESA holes (M6 x 6, 200 mm pitch) (P)
Accessories	Power cable, Remote control, Utility disk(CD-ROM), Vertical logo, Temporary stand, Cable clamp, Power cord clamp, Operation manual, Blank sticker, 2 "AA" size batteries
Material	Front: Resin / Back : Aluminum; (Front bezel replaceable)
Dimensions (W x D x H) with bezel in mm	1,255 × 140 × 743
Dimensions (W x D x H) without bezel in mm	1,255 × 132 × 743
Height	44
Power consumption	325/35
Operating temperature	0 to 40
Operating Humidity	20% to 80% (No-condensing)
Input voltage	100V-240V
Model Code	4,97402E+12